Technical Datasheet elesa® CLEAN K1 K3 IPA Isopropyl Alcohol





• Definition



Isopropyl alcohol in spray for cleaning and degreasing any type of surface. Zero residue. Cleaner for all types of surfaces including metal and plastic.



Sucess Sectors



- Automotive
- √ Food processing sector.
- ✓ Pharmaceutical.
- ✓ Electronic components.
- ✓ Mechanical metal.
- ✓ Energy generation.
- ✓ Naval sector.



- U.S.P. Grade Isopropyl Alcohol so it is suitable for use in the food industry when there may be contact with food.
- ✓ Ideal for cleaning delicate objects affected by humidity.
- ✓ Leaves no residue or moisture when dry.
- √ Very fast evaporation.
- ✓ Improves paint adhesion due to its antistatic quality.
- ✓ Rapid evaporation saving drying times.
- ✓ Powerful degreaser for metal parts.

Quality level

Meet standards:

NSF-K1 K3, FDA 21CFR.17.3570 incidental food contact.

Characteristics

TEST	Specifications
Composition	Propanol-2
Chemical formula	C3H8O
Molecular weight (gr/mol)	60,10
Purity, % mass, mín	99,5
Density 20°C	0,7863
Water, % weight, max.	0,037
Evaporation residue, % m/m	<0,001
Acidity as acetic acid, % m/m	<0,001

The stated characteristics reflect typical values. They should not be taken as product specifications.

Alternative products

For availability of alternative products, consult our technical department.

Formats

Spray

Storage

It is recommended not to store at temperatures above 25°C and below 0°C, store in a dry place that does not give it direct light. It must be kept in the original container.

Safety and hygiene

There is a corresponding Safety Data Sheet in accordance with current legislation, which provides information regarding the dangerousness of the product, precautions in handling, first aid measures and environmental data available

Edition: 04.22

